



21 September 2012  
21 September 2012  
P.U. (A) 310

WARTA KERAJAAN PERSEKUTUAN

*FEDERAL GOVERNMENT  
GAZETTE*

KAEDAH-KAEDAH ISYARAT LALU LINTAS  
(SAIZ, WARNA DAN JENIS) (PINDAAN) 2012

*TRAFFIC SIGNS (SIZE, COLOUR AND TYPE)  
(AMENDMENT) RULES 2012*



DISIARKAN OLEH/  
PUBLISHED BY  
JABATAN PEGUAM NEGARA/  
ATTORNEY GENERAL'S CHAMBERS

## AKTA PENGANGKUTAN JALAN 1987

## KAEDAH-KAEDAH ISYARAT LALU LINTAS (SAIZ, WARNA DAN JENIS) (PINDAAN) 2012

PADA menjalankan kuasa yang diberikan oleh perenggan 88(1)(q) Akta Pengangkutan Jalan 1987 [Akta 333], Menteri, setelah berunding dengan Menteri Kerja Raya, membuat kaedah-kaedah yang berikut:

**Nama dan permulaan kuat kuasa**

1. (1) Kaedah-kaedah ini bolehlah dinamakan **Kaedah-Kaedah Isyarat Lalu Lintas (Saiz, Warna dan Jenis) (Pindaan) 2012**.

(2) Kaedah-Kaedah ini mula berkuat kuasa pada 23 September 2012.

**Pindaan Jadual**

2. Kaedah-Kaedah Isyarat Lalu Lintas (Saiz, Warna dan Jenis) 1959 [L.N. 167/1959] dipinda dalam Jadual—

(a) dalam Bahagian I, di bawah tajuk “DANGER SIGNS”, dengan memasukkan selepas isyarat lalu lintas No. 13W isyarat lalu lintas yang berikut:

No.	Meaning of Sign	Sign
-----	-----------------	------

**“13X. CAMERA OPERATION ZONE**

This sign indicates a camera operation zone at a signalized junction.

**DIMENSIONS:**

Height of lettering (mm)	Dimension of camera box (mm)				Post height (m)
		<i>a</i>	<i>b</i>	<i>d</i>	
80	Minimum	400	10	10	Minimum 1.8
	Maximum	600	10	15	



COLOUR: Yellow background, black borders and letters.

FONT TYPE: Ccridge Narrow.

MATERIAL: High intensity prismatic retroreflective sheeting.

OR

13Xa. CAMERA OPERATION ZONE

This sign indicates a camera operation zone ahead.

DIMENSIONS:

Speed (km/h)	Height of lettering (mm)	Dimension of camera box (mm)		Post height (m)
		<i>a</i>	<i>b</i>	
91 or more	400	750	20	Minimum 2.2
81 to 90	250	600	15	Minimum 2.2
61 to 80	200	500	10	Minimum 1.8
60 or less	150	400	10	Minimum 1.8



COLOUR: Yellow background, black borders and letters.

FONT TYPE: Ccridge Narrow.

MATERIAL: High intensity prismatic retroreflective sheeting.

”; dan

- (b) dalam Bahagian VI, di bawah tajuk “PLACING AND HEIGHT OF ROAD SIGNS”, di bawah kepala “PART I DANGER SIGNS”, dengan memasukkan selepas perenggan (4), perenggan yang berikut:

“(5) Traffic sign No. 13X shall be placed between fifty to five hundred metres from the location of the detector system for a static camera at the signalized junction.

(6) Traffic sign No. 13Xa shall be placed between two to three kilometres from the location of—

(a) the detector system for a static camera; or

(b) mobile camera operation,

as the case may be.

(7) The detector system referred to in paragraphs (5) and (6) refers to the detector system as specified in the Road Transport (Camera-Recorded Offences) Rules 2012 [*P.U. (A) 309/2012*].”.

Dibuat 21 September 2012  
[KP/PUU/0.440/W/BD/9; PN(PU2)460/LXVII]

DATO' SERI KONG CHO HA  
*Menteri Pengangkutan*

ROAD TRANSPORT ACT 1987

TRAFFIC SIGNS (SIZE, COLOUR AND TYPE) (AMENDMENT) RULES 2012

IN exercise of the powers conferred by paragraph 88(1)(q) of the Road Transport Act 1987 [Act 333], the Minister, after consultation with the Minister of Works, makes the following rules:

**Citation and commencement**

1. (1) These rules may be cited as the **Traffic Signs (Size, Colour and Type) (Amendment) Rules 2012**.

(2) These Rules come into operation on 23 September 2012.

**Amendment of Schedule**

2. The Traffic Signs (Size, Colour and Type) Rules 1959 [L.N. 167/1959] are amended in the Schedule—

(a) in Part I, under the title of “DANGER SIGNS”, by inserting after the traffic sign No. 13W the following traffic signs:

No.	Meaning of Sign	Sign
-----	-----------------	------

“13X. CAMERA OPERATION ZONE

This sign indicates a camera operation zone at a signalized junction.

**DIMENSIONS:**

Height of lettering (mm)	Dimension of camera box (mm)				Post height (m)
		<i>a</i>	<i>b</i>	<i>d</i>	
80	Minimum	400	10	10	Minimum 1.8
	Maximum	600	10	15	



COLOUR: Yellow background, black borders and letters.

FONT TYPE: Ccridge Narrow.

MATERIAL: High intensity prismatic retroreflective sheeting.

OR

13Xa. CAMERA OPERATION ZONE

This sign indicates a camera operation zone ahead.

DIMENSIONS:

Speed (km/h)	Height of lettering (mm)	Dimension of camera box (mm)		Post height (m)
		<i>a</i>	<i>b</i>	
91 or more	400	750	20	Minimum 2.2
81 to 90	250	600	15	Minimum 2.2
61 to 80	200	500	10	Minimum 1.8
60 or less	150	400	10	Minimum 1.8



COLOUR: Yellow background, black borders and letters.

FONT TYPE: Ccridge Narrow.

MATERIAL: High intensity prismatic retroreflective sheeting.

”; and

(b) in Part VI, under the title of “PLACING AND HEIGHT OF ROAD SIGNS”, under the heading of “PART I DANGER SIGNS”, by inserting after paragraph (4), the following paragraphs:

“(5) Traffic sign No. 13X shall be placed between fifty to five hundred metres from the location of the detector system for a static camera at the signalized junction.

(6) Traffic sign No. 13Xa shall be placed between two to three kilometres from the location of—

(a) the detector system for a static camera; or

(b) mobile camera operation,

as the case may be.

(7) The detector system referred to in paragraphs (5) and (6) refers to the detector system as specified in the Road Transport (Camera-Recorded Offences) Rules 2012 [*P.U. (A) 309 /2012*].”.

Made 21 September 2012  
[KP/PUU/0.440/W/BD/9; PN(PU2)460/LXVII]

DATO' SERI KONG CHO HA  
*Minister of Transport*